

The Vigor C410/C510 Series is a high-performance Cellular WAN Security Router featuring embedded cellular connectivity for seamless and reliable internet access. Designed as a primary WAN solution, it is set to operate in "Always On" mode by default, ensuring uninterrupted connectivity. It is equipped with advanced features such as VPN, QoS, route policy, web content filtering, Identity and Access Management (IAM), a hotspot web portal, and more.

Cellular WAN 4 VPN 50K Sessions AX3000 (ax model only)



Interface

WAN Port	1 x GbE RJ-45
LAN/WAN Switchable Port	1 x GbE RJ-45
3 LAN Port	3 x GbE RJ-45 (C510 series)
	4 x GbE RJ-45 (C410 series)
4 SIM Slot	2 x Nano-Sized
Button	1 x Factory Reset
	1 x WLAN/WPS (ax model)

Internet Connection

IPv4	PPPoE, DHCP, Static IP
IPv6	PPP, DHCPv6, Static IPv6, TSPC,
	6rd, 6in4 Static Tunnel
802.1p/q Multi-VLAN Tagging	•
Multi-VLAN/PVC	•
Failover	•
Connection Detection	ARP, Ping
WAN Data Budget	•
Dynamic DNS	•
DrayDDNS	•

5G/LTE/WCDMA (C510 series)

	•	, , , , , , , , , , , , , , , , , , ,
5G Band		n1,3,7,8,20,28,38,40,77,78
5G Max. Link Rate		NR SA: 2.4Gbps (DL) / 900Mbps (UL)
		NR NSA: 3.4Gbps (DL) / 550Mbps (UL)
LTE FDD Band		B1,3,7,8,20,28
LTE TDD Band		B38,40
LTE Category		Cat19 (DL) / Cat18 (UL)
LTE Max. Link Rate		1.6Gbps (DL) / 200Mbps (UL)
WCDMA (3G) Band		B1,8

LTE (C410 series)

LTE FDD Band	B1,3,7,8,20,28
LTE TDD Band	B38,40
LTE Category	Cat6
LTE Max. Link Rate	300 Mbps (DL) / 50 Mbps (UL)
WCDMA (3G) Band	B1, 8

For other band availability, please contact your local DrayTek distributor or us.

LAN

VLAN	802.1q Tag-based, Port-based
Max. Number of VLAN	8
LAN Subnet	4
DHCP Server	Multiple IP Subnet, Custom DHCP
	Options, Bind-IP-to-MAC
Wired 802.1x Authentication	•
Port Mirroring	* (Future Support)
Local DNS Server	•
Conditional DNS Forwarding	•
Hotspot Web Portal	•
Hotspot Authentication	Click-Through, External Portal
	Server

WLAN (ax model)

WiFi 6	•
Max. Number of SSIDs	8 per band
Security Mode	OWE, WEP, WPA, WPA2,
	WPA2/WPA, WPA3, WPA3/WPA2
Authentication	Pre-Shared Key
OFDMA	•
Roaming	Assisted Roaming
WPS	WPS Button, PIN Code
WDS	Repeater
Access Control	Access List, Client Isolation,
	Hide SSID, WLAN Scheduling
AirTime Fairness	•
Band Steering	•
WMM	•
Mesh (5GHz Only)	Root

Networking

IPv4 Static Route, IPv6 Static Route,
Policy Route, Inter-VLAN Route, RIP v1/v2,
BGP, OSPF (v2/v3)
Protocol, IP Address, Port
•
IGMP v2/v3, IGMP Proxy, IGMP Snooping
& Fast Leave
•
• (Requires external storage)

Bandwidth Management

Traffic Shaping Policy	•
IP-based Bandwidth Limit	•
IP-based Session Limit	•
QoS (Quality of Service)	IP Address, Port, Application
APP QoS	•
Default Policy	•
VoIP Prioritization	•

IAM

Users & Groups	•
Access Policies	•
Group Policies	•
Conditional Access Policies	•
Resources	•
Account Status	•
Backup and Restore	•

Management

Local Service	HTTP, HTTPS, Telnet, SSH v2, FTP, TR-069
Config Backup/Restore	•
Firmware Upgrade	TFTP, HTTP, TR-069
Role-based Privilege	•
Access Control	Access List, Brute Force Protection
Notification Alert	SMS, E-mail
SNMP	v1, v2c, v3
Syslog	•
Virtual AP Controller	20
Mesh (Number of manageable	7
APs)	
Virtual Switch Controller	5
VigorACS Management	•

Security

IP Reputation Filter	•
Firewall Filter	IP, Content, Traffic
Defense Setup	ARP Spoofing, IP Spoofing
MAC Filtering Profile	•
IPv6 Address Security	•

VPN

Site-to-Site	•
Teleworker VPN	•
EasyVPN	•
Protocols	IPsec, IKEv1/IKEv2, IKEv2-EAP,
	IPsec-XAuth, OpenVPN, WireGuard
Max. VPN Tunnels	4
User Authentication	Local, RADIUS, TACACS+, mOTP, TOTP
IKE Authentication	Pre-Shared Key, X.509
IPsec Authentication	SHA-1, SHA-256
Encryption	AES, DES, 3DES
Single-Armed VPN	•
NAT-Traversal (NAT-T)	•
VPN Connection Status	•
Backup & Restore	•

Monitoring

Clients List	•
Log Center	•
Wireless Information	•
WAN	•
ARP Table	•
Route Table	•
DHCP Table	•
IPv6 TSPC Table	•
IPv6 Neighbor Table	•
DNS Cache Table	•
PPPoE Pass-Through	•
Session Table	•

	WLAN	4G	5G
Vigor C410		•	
Vigor C410ax	•	•	
Vigor C510		•	•
Vigor C510ax	•	•	•

